

Dana 30 Axle Side Bushing Replacement Instructions

JEEPSE Front Axle Dana 30 Control Arm Bushings – Forked End: All Front Dana 30 Axles with Forked Control Arms



1. Remove forked end of the control arm from the axle.
2. Remove the axle bushings from the axle they are pressed in so you may have to use a rubber mallet and wood to remove. **BE CAREFUL NOT TO DAMAGE OUTER METAL SLEEVE YOU WILL RE-USE.**
3. With the bushings removed use a torch or drill (preferred method) with a large drill bit and with the bushing in a vise start to drill out the rubber. After a while you should be able to press the bushing out. This is vulcanized rubber so it may take some time.
4. Install the new bushings into the metal sleeves, use grease if necessary. Then install the bushing assembly into the Dana 30 axle and re-install the forked end of the control arm. Check and retighten nuts periodically.

DISCLAIMER WARNING

When using this product your vehicle will be modified to increase performance. Whenever a modification is done you change the performance of the vehicle including handling, braking, and steering. You should always drive safely and avoid any maneuvers that would cause harm, serious injury or death to the driver or passengers. Note in the case of using larger tires you must readjust your speedometer gear for accurate speed readings. This product is manufactured for off-road use only and should be installed by a professional mechanic. All products carry a lifetime warranty against defects. Please return warranty card. While every attempt is made to ensure that the information contained in these instructions are correct, no liability can be accepted by the authors for loss, damage or injury caused by any errors in, or omissions from the information given. All service should be performed by qualified mechanics. Rukse, LLC, cannot be held responsible for any mechanical work performed. Standard and accepted safety precautions and equipment should be used in every procedure. This modification will cause the vehicle to handle differently than with stock suspension. Unusual maneuvers could cause loss of control. Care must be taken at all times.

Please obey all posted laws, speed limits, and drive safely at all times. Please wear your seat belt at all times.

