

STRATEGICALLY ENGINEERED

PRODUCT INSTRUCTIONS

JEEP WRANGLER JK FRONT AND REAR SPACER KIT

INSTRUCTIONS - Read complete instructions before beginning installation, the following special tools are recommended: Coil spring compressor, floor jack, jack stands, and hand tools.

- 1. Check all parts and lay out the tools. Jack up the front of the vehicle and support the vehicle at the frame with jack stands. Put wheel chocks behind the rear tires.
- 2. With the jack under the front axle jack up the axle and remove the front wheels. Disconnect the shocks and sway bar end links and lower the axle and remove the springs.
- 3. Install the front spacers over the stock isolators and reinstall the front coils. Jack the front axle and reinstall shocks and sway bar end links. On 2" lift install the extended front bump-stops if purchased.
- 4. Place the wheel chock at the front tires and jack up the rear suspension and support the vehicle at the frame and remove the rear tires.
- 5. With the jack under the axle jack it up so you can disconnect the rear shocks and the rear sway bar at the frame.
- 6. Lower the rear axle and remove the coil springs and install the spacer over the stock isolator and reinstall the coil spring.
- 7. Jack up the axle and reinstall the shocks and reinstall sway bar. On 2" lift install the extended rear bumpstops if purchased.
- 8. Put the rear tires on and remove jack stands and put back on the ground.
- 9. You need to have your wheel alignment checked. Check all bolts after 500 miles.

DISCLAIMER WARNING

When using this product your vehicle will be modified to increase performance. Whenever a modification is done you change the performance of the vehicle including handling, braking, and steering. You should always drive safely and avoid any maneuvers that would cause harm, serious injury or death to the driver or passengers. Note in the case of using larger tires you must readjust your speedometer gear for accurate speed readings. This product is manufactured for off-road use only and should be installed by a professional mechanic. All products carry a lifetime warranty against defects. Please return warranty card to be eligible. Thanks for purchasing RüK products.

Please obey all posted laws, speed limits, and drive safely at all times. Please wear your seat belt at all times.

